



GOODWE
your solar engine

ES Series

Bi-directional energy storage



GoodWe ES series bi-directional energy storage inverter is compatible with both on-grid and off-grid PV systems. It can control the flow of energy intelligently. During daytime, the PV plant generates electricity which can be provided to the loads, fed into the grid or charge the battery. The electricity stored can be released when the loads require it during the night. Additionally, the power grid can also charge the storage devices via the inverter.

- Innovative solution for Energy Storage
- Charge controller and inverter integrated
- Intelligent battery management function
- Capable of being grid-interactive or grid-independent
- Compatible with both Lead-acid and Li-Ion battery
- More security & performance for same costs
- Monitoring inverters freely via computers or mobile phones
- Fanless low-noise design
- IP65 dust-proof and water-proof rating
- 45°C full-load output

Technical Data

GW5048D-ES

GW3648D-ES

Solar		
Max. recommended PV Power [W]	6000	4600
Nominal DC Power [W]	5000	4000
Max. DC voltage [V]	580	580
MPPT voltage range [V]	125~550	125~550
Starting voltage [V]	150	150
Max. DC current [A]	11/11	11/11
No. of DC connectors	2	2
No. of MPPTs	2 (can parallel)	2 (can parallel)
DC connector	AMPHENOL/ MC4/ SUNCLIX	AMPHENOL/ MC4/ SUNCLIX
Battery		
Battery type	Lead-acid or Li-Ion	Lead-acid or Li-Ion
Nominal Voltage [V]	48	48
Max Discharge power [W]	4600	3600
MAX Charge power [W]	2300, programmable	2300, programmable
Battery capacity [Ah]	≥ 100 (depending requirement)	≥ 100 (depending requirement)
Charging curve	3-stage adaptive with maintenance	3-stage adaptive with maintenance
Charging voltage [V]	57 (optional)	57 (optional)
Battery temperature compensation	Included (Li-Ion)	Included (Li-Ion)
Battery voltage sense	Integrated	Integrated
Current shunt	Integrated	Integrated
AC Output Data		
Nominal AC power [W]	4600	3600
Max. AC power [W]	4600	3600
Peak power (Back-up) [W]	1.5x Pnom, 10sec	1.5x Pnom, 10sec
Max. AC current [A]	20	16
Nominal AC output	50/60Hz; 230Vac	50/60Hz; 230Vac
AC output range	45~55Hz/55~65Hz; 180~270Vac	45~55Hz/55~65Hz; 180~270Vac
AC output (Back-up)	230Vac ±2%, 50Hz(60Hz optional) ±0.2%, THDv<3% (linear load)	230Vac ±2%, 50Hz(60Hz optional) ±0.2%, THDv<3% (linear load)
THDi	<1.5%	<1.5%
Power factor	0.8 leading~0.8 lagging	0.8 leading~0.8 lagging
Grid connection	Single phase	Single phase
Efficiency		
Max. efficiency	97.6%	97.6%
Euro efficiency	>97.0%	>97.0%
MPPT adaptation efficiency	99.9%	99.9%
Protection		
Residual current monitoring unit	Integrated	Integrated
Anti-islanding protection	Integrated	Integrated
DC switch (PV)	Integrated (optional)	Integrated (optional)
AC over current protection	Integrated	Integrated
Insulation monitoring	Integrated	Integrated
Certifications & Standards		
Grid regulation	VDE-AR-N4105, VDE 0126-1-1, G83/2, G59/3, AS4777.2/3	
Safety	IEC62109-1&-2, AS3100, IEC62040-1	
EMC	EN61000-6-1, EN61000-6-2, EN61000-6-3, EN61000-6-4, EN61000-3-11, EN61000-3-12	EN61000-6-1, EN61000-6-2, EN61000-6-3, EN61000-6-4, EN61000-3-2, EN61000-3-3
General Data		
Dimensions (WxHxD)	516*440*184mm	516*440*184mm
Weight [kg]	30	28
Mounting	Wall bracket	Wall bracket
Ambient temperature range	-25~60°C (>45°C derating)	-25~60°C (>45°C derating)
Relative humidity	0~95%	0~95%
Max. operating altitude	4000m(> 3000m derating)	4000m(> 3000m derating)
Protection degree	IP65	IP65
Topology	Transformerless	Transformerless
Standby losses [W]	<8	<8
Cooling	Natural convection	Natural convection
Noise emission [dB]	<25	<25
Display	LED light & APP	LED light & APP
Communication	USB2.0; WiFi	USB2.0; WiFi
Standard warranty [years]	5	5